




## LMR600® Crimp Tool

### Specifications:

Model Number: 31-CT-L6R  
 Crimp Die: 0.61in (15.5mm) Ferrule & 0.186 (4.72mm) Pin  
 Length: 9in (228mm)  
 Weight: 592 grams  
 Material: Carbon and Hardened Steel with Black Oxide Finish



**We carry numerous connectors for LMR® 600 Cable.  
 Some of these are displayed below. Please call us or visit our website to  
 find out about our complete line of connectors for LMR® 600.**



### 11-01L6-TGS

N Male Clamp,  
Teflon Insulation, Gold Pin,  
Silver Plated Body, Knurled,  
for LMR®600 and equivalent cable

### 11-02L6-TGS

N Female Clamp, Teflon Insulation,  
Gold Pin, Silver Plated Body,  
for LMR®600 and equivalent  
cable



### 11-11L6-TGS

N Male Crimp,  
Teflon Insulation, Gold Pin,  
Silver Plated Body, Knurled,  
for LMR®600 and equivalent cable

### 15-10L6-TGS

TNC Male Crimp, Teflon Insulation,  
Gold Pin, Nickel Plated Body,  
for LMR®600 and equivalent  
cable



### 15-10L6-RP-TGS

TNC Male Crimp, Teflon  
Insulation, Gold Pin, Nickel  
Plated Body, Reverse Polarity  
for LMR®600 and equivalent cable

### 30-01L6-TSSN

7/16 DIN Male Clamp, Teflon  
Insulation, Silver Pin, Nickel Plated  
Body, Knurled, for LMR®600  
and equivalent cable



**We make it easy to check prices and availability!**

Call us at **714.523.8885**, Skype us at **TCCinc3**, or click our live support link at **www.tccinc.com**

TCC Industries Inc 7050 Village Dr unit E Buena Park CA 90621 | 714.523.8885 | www.tccinc.com



## N type Fast Connectors for LMR® series Cable

This connector series is designed specifically for the purpose of making **fast, high quality, low loss connections** when working with Times Microwave LMR® series cable.



**11-11L6-EHK-TGA**  
for LMR®600








**11-11T-EK-TGA**  
for LMR®400

These connectors make your job **easy and fast**. There is no need to waste time crimping or soldering a pin, all you need to do is snap the pin in, push your cable in and crimp the ferrule. You can also use optional heat shrink tubing to further protect your connection.

Additionally, since these are TCC connectors, you can be assured that they are made with the **highest grade materials** and held to the **highest quality standards**. The bodies are silver plated and high quality teflon surrounds the pin insulating your signal against loss, the pin itself is gold plated to ensure a solid and consistent connection.

TCC also has crimping tools available for these connectors.

	<b>31-HT-336K</b>			
	 0.429" (10.9mm)	 0.128" (3.25mm)	 0.1" (2.54mm)	
For LMR®400			For LMR®600	

**We make it easy to check prices and availability!**

Call us at **714.523.8885**, Skype us at **TCCinc3**, or click our live support link at **www.tccinc.com**

TCC Industries Inc 7050 Village Dr unit E Buena Park CA 90621 | 714.523.8885 | www.tccinc.com